

Masterclock®

NTP Driven Clocks

NTDS8646



STANDARD FEATURES

- > 7 in (18 cm) 6-digit LED top display with 4" (10.2cm) 6-digit bottom display available in red, green, blue or amber
- > Syncs to any NTP source for accurate traceable time
- > Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- > Configures to time zone and daylight saving time parameters
- > WinDiscovery software utility included - provides easy configuration of clocks and generators attached to network
- > Fully configurable network settings, including DHCP / BOOTP / STATIC IP
- > Configuration is saved to non-volatile memory and survives power losses
- > Password protection prevents unauthorized clock configuration tampering
- > Display time in 12- or 24-hr format – hh:mm:ss
- > Display date – mm:dd:yy, dd:mm:yy or yy:mm:dd – configurable
- > Adjustable brightness levels with auto-dimming option
- > Visibility: 350 ft (100 m)
- > Stainless steel chassis
- > Wall-mount bracket
- > Dry contact relay option
- > PM indicator

SPECIFICATIONS

Connectors

- > Ethernet RJ45
- > IEC AC Power
- > USB for configuration

Power

- > International IEC AC 90-240v, 50/60 Hz
- > Power consumption < 15W

Operating Parameters

- > Temperature: 0 to 60°C
- > Humidity: Up to 90% (non-condensing)

Physical

- > Stainless steel chassis
- > Size: 39.4w x 15h x 2.63d in (100w x 38h x 6.7d cm)
- > Weight: 24 lbs (11 kg)

Compliance

- > FCC, ROHS, CE Marked, ANSI



The optional **RC600** (above) is a remote control that adds both count-down and count-up timer control features to our NTDS and TCDS clocks. Uses WinDiscovery software.

MASTERCLOCK, INC.

5-YEAR LIMITED PARTS & LABOR WARRANTY

MADE IN THE USA

phone (USA and Canada):
1-800-940-2248

phone (international):
+1-636-724-3666

email:
sales@masterclock.com

online:
www.masterclock.com