



STANDARD FEATURES

- > 1-in (2.5 cm) 12-digit LED display available in red, green, blue or amber
- > Reads IRIG-B, SMPTE 12M, 309M, 24/25/30 fps, 29.97 drop frame
- > Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- > Configures to time zone and daylight saving time parameters
- > WinDiscovery software utility included – provides easy configuration of clocks
- > Configuration is saved to non-volatile memory and survives power losses
- > Password protection prevents unauthorized clock configuration tampering
- > Display time in 12- or 24-hr format – hh:mm:ss
- > Display date – mm:dd:yy, dd:mm:yy or yy:mm:dd
- > Configurable to alternate showing date and time automatically
- > Adjustable brightness levels
- > Visibility: 50 feet (15 meters)
- > Dry contact relay option
- > PM indicator

OPTIONS

- > Surface mount (desktop version)
- > Rack-mount (TCDS112 -RM)

SPECIFICATIONS

Connectors

- > BNC female
- > 3-pin terminal block
- > USB for configuration
- > DC input – 2.1 mm female
- > IEC C5 A/C Power

Power

- > Choice of – IEC AC or DC (24VDC)
- > International IEC AC 90-240v, 50/60 Hz
- > Power consumption < 8W

Operating Parameters

- > Temperature: 0 to 60°C
- > Humidity: Up to 90% (non-condensing)

Physical

- > Black powder-coated steel chassis
- > Surface mount (desktop version)
 - Size: 17w x 1.75h x 4.5d in (43.2w x 4.5h x 11.4d cm)
 - Weight: 2.0 lbs (0.9 kg)
- > Rack-mount
 - Size: 16.9w x 1.7h x 3.5d in (43w x 4.31h x 8.9d cm)
 - Weight: 1.73 lb (0.78 kg)

Compliance

- > FCC, ROHS, CE Marked, ANSI



The optional **RC600** (above) is a remote control that adds both count-down and count-up timer control features to our NTDS and TCDS clocks. Uses WinDiscovery software.